

Valve Cover Racing Rules

Stock

Must use small block Chevrolet valve cover.
Must be short type only.
Can be steel or aluminum.
Must be stock in appearance (no wings, etc).
Maximum width 10 inches.
Maximum weight 5 pounds.

Modified

Must be small block Chevrolet valve cover.
Can be tall or short.
Can be steel, aluminum, cast, or carbon fiber.
Maximum width 10 inches.
Maximum weight 7 pounds.

Unlimited

Can be small or big block.
Chevrolet or other make.
Can be tall or short.
Can be any material.
Maximum width 11.5 inches
Maximum weight 15 pounds.

Rules and Specifications

Valve Covers

NO engines or motors are allowed.
GRAVITY power only.
Leading edge of racer must contact track
Starting pin (pin extends 2 inches above track)
All entries must be officially weighed in.
Valve Covers must pass a technical inspection.
Valve Covers must have a minimum of 3 wheels.
Individual entries are allowed in one class only.

Track

Will be 20-30 feet long.
Starting line will be 4 feet off the floor.
Lanes will be 12 inches wide.
Rails will be 2 inches high.
Races will be electronically timed, when Possible.
Eliminations will proceed after time trials
And qualifying runs completed.

*****all track measurements are approximate*****

General

Entrants are responsible for staging their own Valve Cover entry.
Racing is open to kids of all ages, one official entry per person, after time trials.
Unsportsmanlike conduct will result in disqualification (& heavy shame).
Organizers do not accept responsibility for injury or damage to persons or property.
Decisions of the Organizers will be final. Protests will NOT be acknowledged.
Awards **MAY** be made for People's Choice, Rusty Wheels, etc, & Competition Classes.

Anything NOT specifically PROHIBITED by above rules is LEGAL.
Anything NOT specifically REQUIRED by above rules is OPTIONAL.
If you have any questions, ask the Organizers.